


# 6x19 Seale

## DRILL LINE 6x19S (9/9/1)

Designed to provide excellent strength and resistance to abrasion, making it well-suited to be used as a rotary drill line.

- 19 to 26 wires per strand.
- Flexibility and wear resistance.
- Provides great ruggedness and resistance to abrasion and crushing.
- Special lubricant that works on all different environments.



Diameter (in)	Diameter (mm)	Weight (lb/ft)	Minimum Breaking Force (tons for 2000 lbs)	
			EIPS 1960	EEIPS* 2160
7/8	22.2	1.42	39.8	43.8
1	25.4	1.85	51.7	56.9
1 1/8	28.6	2.34	65.0	71.5
1 1/4	31.8	2.89	79.9	87.9
1 3/8	34.9	3.50	96.0	106
1 1/2	38.1	4.16	114	125
1 5/8	41.3	4.88	132	146
1 3/4	44.5	5.67	153	169
1 7/8	47.6	6.50	174	192
2	50.8	7.39	198	217

### Available as Standard

Lay Type	
Regular	Lang
<input checked="" type="radio"/>	<input type="radio"/>

Lay Direction	
Right	Left
<input checked="" type="radio"/>	<input type="radio"/>

Finish	
BRT	GALV
<input checked="" type="radio"/>	<input type="radio"/>

Grade	
EIPS	EEIPS
<input checked="" type="radio"/>	<input type="radio"/>

\*EEIPS made to order.  
Contact your local representative for availability.

### Standard Lubricants

LUBE - A | Our lightest standard lube for enhanced handling.

LUBE - B | Excellent lubricity and corrosion protection.

LUBE - C | Heavy lube designed to give extra lubrication, corrosion protection, enhanced durability, and reduced wear and heat generation.

LUBE - D | Heavy C lube that is also applied at stranding process. Creates heaviest standard coat available for elevated heat and winter conditions.

SPECIAL LUBES | Specialty lubes available upon request.

