


6x25 & 6x26 Swaged Compacted

6x26WS (10/5 & 5/5/1)

Compacted strand wire rope is designed for logging and material handling applications where strength and improved wear resistance are required.

- Better drum performance.
- Abrasion resistance.
- Greater strength.



Diameter (in)	Weight (lb/ft)	Minimum Breaking Force (tons for 2000 lbs)
		EEIPS* 2160
1/2	0.65	18.6
9/16	0.81	23.5
5/8	0.95	28.8
3/4	1.43	40
7/8	1.92	52
1	2.37	68
1 1/8	2.96	85
1 1/4	3.51	102
1 3/8	4.12	120

Available as Standard

Lay Type		
Regular	Lang	Alt
●		

Lay Direction	
Right	Left
●	

Finish	
BRT	GALV
●	

Grade	
EIPS	EEIPS
●	

*EEIPS made to order.
Contact your local representative for availability.

Standard Lubricants

LUBE - A | Our lightest standard lube for enhanced handling.

LUBE - B | Excellent lubricity and corrosion protection.

LUBE - C | Heavy lube designed to give extra lubrication, corrosion protection, enhanced durability, and reduced wear and heat generation.

LUBE - D | Heavy C lube that is also applied at stranding process. Creates heaviest standard coat available for elevated heat and winter conditions.

SPECIAL LUBES | Specialty lubes available upon request.



Logging Industry