


6x26 & 6x31 IWRC

TUBING LINES 6x26WS (10/5 & 5/5/1)

High performance lubrication for durability in the harshest environments.

- High resistance.
- Used as a hoist rope in elevator applications.



Diameter (in)	Construction	Weight (lb/ft)	Minimum Breaking Force (tons for 2000 lbs)	
			EIPS 1960	EEIPS* 2160
7/8	6x26 Swaged	1.7	47.8	52.6
7/8	6x31 Swaged	1.7	47.8	52.6
1	6x26 Swaged	2.22	62	68.2
1	6x31 Swaged	2.22	62	68.2
1 1/8	6x31 Swaged	2.66	79.3	87.2

Available as Standard

Lay Type	
Regular	Lang
●	

Lay Direction	
Right	Left
●	

Finish	
BRT	GALV
●	

Grade	
EIPS	EEIPS
●	

*EEIPS made to order.
Contact your local representative for availability.

Standard Lubricants

LUBE - A | Our lightest standard lube for enhanced handling.

LUBE - B | Excellent lubricity and corrosion protection.

LUBE - C | Heavy lube designed to give extra lubrication, corrosion protection, enhanced durability, and reduced wear and heat generation.

LUBE - D | Heavy C lube that is also applied at stranding process. Creates heaviest standard coat available for elevated heat and winter conditions.

SPECIAL LUBES | Specialty lubes available upon request.



Oilfield Applications