


6x26 Swaged

6x26WS (10/5 & 5/5/1)

Swaged wire ropes are commonly used in the logging industry for a variety of purposes due to their durability, strength, and resistance to abrasion.

- High-density construction.
- Abrasion resistance.
- Greater strength.



Diameter (in)	Weight (lb/ft)	Minimum Breaking Force (tons for 2000 lbs)
		EEIPS* 2160
7/8	1.70	47.4
1	2.22	62.0
1 1/8	2.80	73.5
1 1/4	3.40	90.0

Available as Standard

Lay Type		
Regular	Lang	Alt
●		

Lay Direction	
Right	Left
●	

Finish	
BRT	GALV
●	

Grade	
EIPS	EEIPS
●	

*EEIPS made to order.
Contact your local representative for availability.

Standard Lubricants

LUBE - A | Our lightest standard lube for enhanced handling.

LUBE - B | Excellent lubricity and corrosion protection.

LUBE - C | Heavy lube designed to give extra lubrication, corrosion protection, enhanced durability, and reduced wear and heat generation.

LUBE - D | Heavy C lube that is also applied at stranding process. Creates heaviest standard coat available for elevated heat and winter conditions.

SPECIAL LUBES | Specialty lubes available upon request.



Logging Industry