


8x19 Class

ROTATION RESISTANT

8x19S (1/2" - 3/4") | 8x26WS (1/2" - 3/4")

The size relationship between strands and cores gives these ropes increased bendability over six strand ropes of the same diameter.

- Crush and rotation resistant rope.
- Increased bendability.
- Used as a hoist rope in elevator applications.



Diameter (in)	Diameter (mm)	Weight (lb/ft)	Minimum Breaking Force (tons for 2000 lbs)	
			EIPS 1960	EEIPS* 2160
1/2	12.7	0.47	10.1	11.6
9/16	14.3	0.60	12.8	14.7
5/8	15.9	0.73	15.7	18.1
3/4	19.1	1.06	22.5	25.9
7/8	22.2	1.44	30.5	35.0
1	25.4	1.88	39.6	45.5
1 1/8	28.6	2.39	49.8	57.3
1 1/4	31.8	2.94	61.3	70.5

Available as Standard

Lay Type	
Regular	Lang
<input checked="" type="radio"/>	<input type="radio"/>

Lay Direction	
Right	Left
<input checked="" type="radio"/>	<input type="radio"/>

Finish	
BRT	GALV
<input checked="" type="radio"/>	<input type="radio"/>

Grade	
EIPS	EEIPS
<input checked="" type="radio"/>	<input type="radio"/>

*EEIPS made to order.
Contact your local representative for availability.

Standard Lubricants

LUBE - A | Our lightest standard lube for enhanced handling.

LUBE - B | Excellent lubricity and corrosion protection.

LUBE - C | Heavy lube designed to give extra lubrication, corrosion protection, enhanced durability, and reduced wear and heat generation.

LUBE - D | Heavy C lube that is also applied at stranding process. Creates heaviest standard coat available for elevated heat and winter conditions.

SPECIAL LUBES | Specialty lubes available upon request.



General Purpose